

|                       |  | A   |   | B  | C  |
|-----------------------|--|---|---|--|--|
|                       |  | TUB UNITS   |   | INLET FILTERS  | OUTLET FILTERS   |
|                       |  | SIZES   | MATERIAL  |  |  |
| <b>TUB ASSEMBLIES</b> | <b>FILTER BAG OPTIONS</b>  | 2 Litre Tub and Base Unit   | Glass 50035006<br>Stainless Steel 50035005  | SS 60 Mesh Support Filter (50035113) with 45 Micron Nylon Inlet Filter (50035110) as standard;<br><br>Also available<br>SS 250 Mesh 50035114<br><br>SS 500 Mesh 50035115   | <b>Large Filter Bags</b><br><br>Nomex 50035407<br>Nylon 50035400<br>Polypropylene 50035404<br>Terylene 50035402  |
|                       |  | 5 Litre Tub and Base Unit   | Glass 50035009<br>Stainless Steel 50035008  |  |  |
|                       |  | Tub assembly 5 Litre with GL32 port supplied with screw fitted blank plate<br><i>To fit <u>Humidity Probe 50186500</u></i>                      | Glass 50035010 (Must use Model 501 FBD to use Humidity Probe)   |  |  |
|                       |  | Multi Tub Unit 50035011   | Stainless Steel Tubs 4 X 50035012   |  |  |
|                       | Glass Tubs 4 X 50035013  |   | SS 60 Mesh Support Filter (50035309) with 45 Micron Nylon Inlet Filter (50035305) as standard;<br>Also available<br>SS 250 Mesh 50035307<br>SS 500 Mesh 50035308<br>3 Micron Polyester 50035306 |  |  |
|                       | <b>SEALED TUB OPTIONS</b><br><small>(Includes Silicon "O" ring &amp; ground glass flange with clamp)</small> | 5 Litre Sealed Glass Tub and Base with Clamp (50035014)   |   | SS 60 Mesh Support Filter (50035113) with 45 Micron Nylon Inlet Filter (50035110) as standard;<br><br>Also available<br>SS 250 Mesh 50035114<br><br>SS 500 Mesh 50035115   | Top Cap with 45 Micron Nylon Filter 50035020<br><br>Top Cap with SS 250 Mesh Filter 50035021<br><br>Top Cap with SS 500 Mesh Filter 50035022<br><br>Top Cap with Nylon Filter Bag 50035023<br><br>Top Cap + 3 Micron Polyester Filter 50035024 |
|                       |  | Tub Assembly 5 Litre Glass Moisture Analysis (Includes ports for sample and Humidity Probe. Both ports supplied with screw fitted blank plates) | Glass 50135020 (Must use Model 501 FBD to use Humidity Probe <u>50186500</u> )  | 3 Micron Polyester Filter for smallest particle size 50035120  |  |
|                       |  | Low Density Classifier Assembly   | Glass Tub 50035049  |  |  |
|                       |  | Multi Tub Unit 50035011   | Glass Tub 4 x 50035033  | Mini Tub, Sealed Tub, Inlet and Outlet sets<br>Mini 45 Micron Nylon Filter <b>Set</b> 50035310<br>Mini 3 Micron Polyester Filter <b>Set</b> 50035311<br>Mini SS 250 Mesh Filter <b>Set</b> 50035312<br>Mini SS 500 Mesh Filter <b>Set</b> 50035313<br>(SS 60 Mesh Support Filter (50035309) and 45 Micron Nylon Inlet Filter (50035305) as standard) |  |