



Consistometer

QUOTE REQUEST



BUY ONLINE



The economical, accurate method of checking viscosity

The Consistometer is a low cost, durable, instrument for accurately checking laboratory or production samples against consistency, viscosity or flow rate standards.

It uses little bench space yet is probably the simplest, most accurate method of conducting a variety of flow associated tests. It is already widely used in the chemical, paint, cosmetic and food processing industries.

It provides a single parameter for a variety of flow tests which can be carried out over any period under as near identical conditions as possible.

The Consistometer is manufactured from stainless steel engraved with a series of precise graduations at 0.5 cm intervals.

To ensure accurate reproducibility the instrument is levelled using the adjustment screws and spirit level.

The instrument is sometimes known as a "Bostwick Consistometer".

Advantages

- Levelling screws and spirit level enable accurate set up
- Engraved graduations for accurate results
- Available in 2 versions - Standard or Extended
- Requires up to 100 ml of sample
- Low cost, ease of use



Specifications	Standard Consistometer	Extended Consistometer
Overall length	355 mm	415 mm
Overall width	84 mm	84 mm
Trough length	240 mm	300 mm
Inside / Outside trough width	49.9 / 51.7 mm	49.9 / 51.7 mm
Min. / Max. height	110 / 139 mm	110 / 139 mm
Material	Stainless Steel	Stainless Steel

Method of use



A measured sample up to 100 ml is placed in the reservoir behind the gate.



The gate is released by pressing the lock release lever - the spring action ensures it opens instantaneously.



As the fluid flows down the instrument its progress can be accurately measured using the graduated scale. By comparing the flow rate to specified time periods the physical properties of the sample can be calculated.